


Mag690[®]

Three-Axis Magnetic Field Sensors






Mag690® Three-Axis Magnetic Field Sensors

These compact and versatile analogue fluxgate sensors provide measurements of static and alternating fields up to 1mT.

A flying lead version is available.



Bartington is a registered trade mark of Bartington Holdings Limited in the following territories: Argentina, Australia, Brazil, Canada, Chile, China, European Union, Hong Kong, Iceland, India, Israel, Japan, Malaysia, Mexico, New Zealand, Norway, Russia, Singapore, South Korea, Switzerland, Taiwan, Turkey, United Kingdom, United States of America, and Vietnam.

Bartington is used under licence by Bartington Instruments Limited.


Mag690 is a registered trade mark of Bartington Holdings Limited in the following territories: Japan, United Kingdom, and United States of America.

Features

- Noise $\leq 25 \text{ pT rms}/\sqrt{\text{Hz}}$ at 1 Hz (range dependent)
- Frequency response from DC to in excess of 1 kHz
- Measuring ranges from $\pm 100 \mu\text{T}$ to $\pm 1000 \mu\text{T}$

Typical Applications

- Detection of magnetic materials
- Traffic monitoring
- MRI site surveying
- Background field measurement



Product Identification

Product name	Connector	Range in μT
Mag690®	<i>No code</i> = Circular connector FL = Flying Lead U = Unpackaged	± 100 ± 500 ± 1000

Example: Mag690-FL100 is a $\pm 100\mu\text{T}$ sensor with flying lead.

Mag690® Specifications

Performance			
Number of axes	Three (right hand XYZ coordinate system)		
Polarity	+ve non-inverting output when pointing North		
Measuring range	$\pm 100\mu\text{T}$	$\pm 500\mu\text{T}$	$\pm 1000\mu\text{T}$
Bandwidth (-3dB)	>1.5kHz		
Measurement noise floor	$\leq 25\text{pTrms}/\sqrt{\text{Hz}}$ at 1Hz	$\leq 35\text{pTrms}/\sqrt{\text{Hz}}$ at 1Hz	$\leq 40\text{pTrms}/\sqrt{\text{Hz}}$ at 1Hz
Scaling	100mV/ μT	20mV/ μT	10mV/ μT
Scaling temperature coefficient	$\pm 115\text{ppm}/^\circ\text{C}$		$\pm 200\text{ppm}/^\circ\text{C}$
Start-up time	150ms		
Warm-up time	15mins		
Offset	$\pm 100\text{nT}$	$\pm 250\text{nT}$	$\pm 500\text{nT}$
Offset temperature coefficient	$\pm 2\text{nT}/^\circ\text{C}$	$\pm 5\text{nT}/^\circ\text{C}$	$\pm 10\text{nT}/^\circ\text{C}$
Scaling error	$\pm 1\%$		
Orthogonality error	<1°		
Alignment error (to mounting face)	<2°		
Linearity error	0.01% (least squares fit)		
Frequency response	DC to 100Hz, maximum flat response ($\pm 5\%$)		
Hysteresis	<2nT for exposure to up to 2 x full scale		
Excitation Breakthrough	<10mV pk-pk at 15.625kHz typical		

Environmental	Mag690®	Mag690FL	Mag690U
Operating temperature range	-20°C to +70°C		
Storage temperature	-20°C to +70°C		
IP Rating	IP67	IP67 (excluding connector)	N/A
Humidity	Up to 90%, non-condensing (unpackaged version)		
Compliance	EMC BS EN 61326:2013 & RoHS		

Mechanical	Mag690 [®]	Mag690-FL	Mag690U
Dimensions excl. cable (WxHxL)	32 x 32 x 122mm		26 x 22 x 94mm
Integral cable length	500mm (incl. connector)	550mm	N/A
Weight (approximate)	220g	200g	20g
Enclosure material	Black acetal and polyurethane potting compound		FR4 PCB Material
Connector	Binder 99 9125 60 08 on 500mm lead	Flying leads 7x0.22mm ²	AMP 3-640456-7
Mating connector	Binder 99 9126 60 08	N/A	AMP 3-640441-7
Cable bending radius	41mm		N/A
Mounting arrangement	4 x M2.5 tapped holes		2 x M2.5 on coil block

Electrical	
Supply voltage	±12V to ±17V DC
Current consumption (max)	+44mA, -16mA (+1.5mA/100 µT on each axis)
Power-on surge	+200mA at +12V, -40mA at -12V
Analogue output	±10V (unbalanced, single ended ref. 0V)
Output impedance	10Ω
Maximum load capacitance	<1µF
Maximum cable length	1.5km (±12V at the pins)

Power Supplies

The Mag690[®] range is compatible with the following data acquisition and power supply units from Bartington Instruments:

- PSU1 Power Supply Unit
- DecaPSU Power Supply Unit (adaptor cable required)
- Magmeter-2 Power Supply and Display Unit
- Spectramag-6 Data Acquisition Unit
- SCU1 Signal Conditioning Unit

Accessories

	Mag690 [®]	Mag690-FL
Cables	Optional extra	N/A
Mating connectors	Not supplied	N/A

The specifications of the products described in this brochure are subject to change without prior notice.

Bartington Instruments Ltd
5, 8, 10, 11 & 12 Thorney Leys Business Park
Witney, Oxford OX28 4GE. England

Telephone: +44 (0)1993 706565
Email: sales@bartington.com

 **Bartington**[®]
Instruments